

# MSCC



- IP20 enclosed Steel body
- White powder coated steel body
- Cat2 Style Louvre
- Dimmable versions available
- Integral Emergency Version
- Ultra High Purity Aluminium Louvre (60° cut off)

T5 Fluorescent surface luminaire for use in offices, reception areas, retail outlets and meeting halls. The body is white powder coated steel with a louvre made from ultra high purity aluminium with white perforated baffles.

Designed to be surface mounted.

Available in 4x14W, 4x24W, 4x28W & 4x54W as well as 2x28w, 2x54W, 2x35W & 2x49W versions.

Can be supplied with integral 3hr emergency, can be fitted with integral occupancy sensor and is also available in a dimmable version.

## ORDER CODES

4 x 14W	2ft 4x14w cat2 surface modular	MSCC414
4 x 24W	2ft 4x24w cat2 surface modular	MSCC424
4 x 28W	4ft 4x28w cat2 surface modular	MSCC428
4 x 54W	4ft 4x54w cat2 surface modular	MSCC454
2 x 28W	4ft 2x28w cat2 surface modular	MSCC228
2 x 54W	4ft 2x54w cat2 surface modular	MSCC254
2 x 35W	5ft 2x35w cat2 surface modular	MSCC235
2 x 49W	5ft 2x49w cat2 surface modular	MSCC249
	1-10v dimming	/DIM
	DALI dimming	/DALI
	DSI dimming	/DSI
	3hr emergency	/EM
	occupancy sensor	/OCC

## S P E C I F I C A T I O N

Rigid steel constructed fluorescent luminaire fully enclosed and powder coated in white finish c/w ultra high purity aluminium reflector. Integral emergency, High Frequency digital or analogue dimming.

Surface mounting. Supplied less lamp.

As Preslite MSCC Range.