

MSCAA



- Suspended (Kit Supplied)
- White coated steel body
- Perforated steel Diffuser
- Dimmable versions available
- Integral Emergency Version
- Integral Occupancy Sensor

Direct/Indirect T5 architectural fitting designed to be suspended (kit supplied). The light distribution is 55% Up/45% Down. All steel construction in a white finish with a perforated central basket type diffuser. Ideally suited to offices, conference rooms and educational establishments. Designed to aid in compliance with LG7 design requirements. IP20 Rated, CE Marked and compliance with all relevant standards including BSEN 60598

ORDER CODES

2x28w	4ft twin suspended T5 direct/indirect	MSCAA228
2x54w	4ft twin suspended T5 direct/indirect	MSCAA254
2x35w	5ft twin suspended T5 direct/indirect	MSCAA235
2x49w	5ft twin suspended T5 direct/indirect	MSCAA249
	Integral Emergency	/EM
	1-10v Dimming	/DIM
	DALI Dimming	/DALI
	DSI Dimming	/DIG
	Integral Occupancy Sensor	/OCC

SPECIFICATION

Rigid steel constructed fluorescent luminaire fully enclosed and coated in white finish c/w perforated steel diffuser, for use with 2 x T5 Lamps in the range 28w/54w/35w/49w integral emergency available, High Frequency digital or analogue dimming option.. Suspended mounting supplied with suspension fixing kit.

As Preslite MSCAA Range.



Tel. +44 1204 575100
Fax. +44 1204 574100

email : sales@saturnlighting.co.uk
<http://www.saturnlighting.co.uk>